

EMERGENCY STOP BUTTON & AUDIO VISUAL BEACON

SQUARE ™
by Schneider Electric



MODEL: 9001KR9R



MODEL: AV1-LED

Main	
range of product	Harmony 9001K
product or component type	Head for spring return push-button
device short name	9001K
operator profile	Flush, red
operator additional information	Full guard in metal
Complementary	
mounting diameter	1.18 in (30 mm)
shape of signaling unit head	Round
type of operator	Spring return
Ordering and shipping details	
Category	21426 - 9001 K (NOT KA,KM,KX)
Discount Schedule	CS1
GTIN	00785901320128

Features and Specifications

- Incandescent light source with integrated horn
- Flash rate 65 fpm
- Shatter-resistant double fresnel polycarbonate lens
- Cast base can function as a junction box
- Suitable for use in indoor and outdoor applications
- Horn is 95dB at 1 meter/85dB at 10ft.
- Option for panel, conduit or box mounting
- Operating temperature range: -31 °F to 150°F (-35°C to 66°C)

HydroTher 

www.HydroTher.com

5170A TIMBERLEA BLVD., MISSISSAUGA, ONTARIO, CANADA L4W 2S5

Phone: (905) 890-3111



Toll Free: 1 (800) 891-5811