

FLOWVIS FLOWMETER



Key Features

- Installation flexibility; installs horizontally, vertically, or even upside-down
- Can be installed with little-to-zero straight pipe requirements with no effect on accuracy
- ≥98% accuracy across the entire model range
- Models available for 1.5" - 8" and metric units for DN40 - DN200
- More NSF 50 certified models than any other brand of flow meter
- Doubles as a check valve (1.5", 2", 2.5" and 2"x2.5" models)
- The first - and only - flow meter for pools and spas to be outdoor-rated by NSF
- Clear, easy-to-read scale in GPM or optional LPM or M3/h with velocity scale
- Installs quickly and easily with no calibration required
- Manufactured in the USA
- 15-year design life, 3-year warranty

FLOWVIS® MODELS

Feature	FV-15	FV-15-U	FV-2	FV-2-U	FV-25	FV-3	FV-3-40	FV-4	FV-6	FV-8
NSF 50 Certified	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
Pipe Size	1.5"	1.5"	2"	2"	2.5"	3"	3"	4"	6"	8"
Operating Range (GPM)	10-80	10-90	10-110	10-110	10-110	70-240	70-240	150-460	300-1000	600-1800
Average Accuracy	98.7%	98.7%	99.4%	99.0%	99.2%	98.9%	99.2%	99.6%	98.1%	N/A*
NSF 50 Level	L1	L1	L1	L1	L1	L1	L1	L1	L1	L1

Hydro Ther

www.HydroTher.com