

# PARAMOUNT SDX2 RETO MAIN DRAIN



## FEATURES AND BENEFITS

- **NO SUMP REQUIRED = TIME SAVED.** No need to field fabricate a sump to meet the '1.5 times the pipe diameter' requirement.
- **Low velocity** 1.396 feet per second at the maximum (188 gpm) flow rating.
- Patented ribbed design achieves very high flow via 60 independent flow partitions.
- Approved as a bulkhead fitting as the safety is in the cover and back plate.
- Anti-vortex center shield blocks contact with direction suction.
- **SDX2 Retro** comes with adaptable back plate to retrofit suction fittings up to 10" in diameter.

# drains	Maximum Flow: Floor	Maximum Flow: Wall
1 SDX2 drain	188 GPM (711 LPM)	154 GPM (582 LPM)
2 SDX2 drains	188 GPM (711 LPM)	154 GPM (582 LPM)
3 SDX2 drains	282 GPM (1066 LPM)	231 GPM (873 LPM)
4 SDX2 drains	376 GPM (1422 LPM)	308 GPM (1164 LPM)

# HydroTher

[www.HydroTher.com](http://www.HydroTher.com)

5170A TIMBERLEA BLVD., MISSISSAUGA, ONTARIO, CANADA L4W 2S5

Phone: (905) 890-3111



Toll Free: 1 (800) 891-5811